

Stand-alone Reader / Dummy Reader

Product synopsis

Door locking device controlling entry
Electric door access control
Access control device that is compatible with Auto door

GM-100 , GM-100PK (Water proof)



MSIP-CMM-Gnp-GM-100
MSIP-REM-Gnp-GM-100PK



GM-200



HU-2000



■ Specifications

Item	Spec
Capacity for card	7000
Capacity for password	4~15digits , up to 100
Frequency	13.56Mhz
Power supply	AC, DC 12V~24V
Current	240~270mA Stand-by : 110mA
Size	150mm* 50mm*40mm

- GM-100 : water proof, single type RF reader (card&digital key)
- GM-100 PK : water proof single type reader only for digital key

■ Specifications

Item	Spec
Capacity for card	300
Capacity for password	4~15digits , up to 10
Frequency	13.56Mhz
Power supply	DC 12V
Current	240~270mA Stand-by : 110mA
Size	132mm* 76.5mm*22mm

■ Specifications

Item	Spec
CPU	32bit RISC
FAR / ARR	0.0001% / 0.1%
Recognition time	within 1sec
Maximum registration	16,000 people (including 2,000 finger prints)
Communication	USB disk
Recognition distance	approx. 10cm
LCD	2.0" TFT Color LCD Type
Power supply	12~24V DC, Max 300mA
Environment	0 ~ 60℃
Size	45mm*180mm*32mm